




# PLANK HARDWOOD FLOORING I TECHNICAL INFORMATION

Product # 1172-3842-10



## WHITE BREATHE COLLECTION DECOR | AQUA WHITE

**Wood species** | Oak  
**Selection** | 1 Natur  
**Constructions** | 3-layer flooring T&G  
**Size** | 15x190x600...2100 mm (5/8"x7 1/2"x2'...7')  
**Finish** | Silk mat finish

### CONSTRUCTION: 3-LAYER FLOORING T&G

| DIMENSIONS :   |                      |           | PACKAGING :          |                       |
|----------------|----------------------|-----------|----------------------|-----------------------|
|                |                      |           | BOX                  | PALLET                |
| Thickness      | 15 mm (5/8")         | Content   | 2,26 m2              | 40 box (90,4 m2)      |
| Width          | 190 mm (7 1/2")      | Weigh     | 23 kg                | 946 kg                |
| Length         | 600...2100 (2'...7') | H x W x L | 100 x 225 x 2 165 mm | 1134 x 905 x 2 165 mm |
| Average length | 1.19 m (3 7/8')      | Content   | 24,318 sq.ft.        | 972,704 sq.ft.        |
| Microlevel     | 0,5 mm               | Weigh     | 24 lb                | 958 lb                |
| Joint type     | T&G                  | H x W x L | 4" x 9" x 86" mm     | 46" x 33" x 86" mm    |

### DEVIATIONS:

|                        |                           |                        |
|------------------------|---------------------------|------------------------|
| Deviation on Thickness | ± 0,2 mm                  | EN 13489<br>FOCT 862.3 |
| Deviation on Width     | ± 0,2 mm                  |                        |
| Height Difference      | ≤ 0,2 mm on 100 mm length |                        |
| Cup                    | ≤ 0,2 % of width          | EN 13489               |
| Bow                    | ≤ 0,5 % of length         |                        |
| Spring                 | ≤ 0,1 % of length         |                        |

### CHARACTERISTICS:

|                             |               |          |
|-----------------------------|---------------|----------|
| Fire resistance             | Dfl-s1        | EN 14342 |
| Formaldehyde emission class | E1            |          |
| Pentachlorophenol content   | None          |          |
| Thermal resistance          | 0,095 m2 K/W  |          |
| Thermal conductivity        | 0,158 W/(m·K) |          |
| Structural warranty         | Lifetime      |          |

### УСТАНОВКА:



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level. Suitable for installation over radiant heating systems.

### УСЛОВИЯ ЭКСПЛУАТАЦИИ И ХРАНЕНИЯ:



— Air humidity 40% – 65%  
— Temperature +18 °C – +22 °C

### FINISH: SILK MAT FINISH

### GRADE: 1 NATUR

| DESCRIPTION:     |   | DESCRIPTION:   |                                     |
|------------------|---|----------------|-------------------------------------|
| Sound sapwood    | Non-contrasting sapwood is allowed up to 25% of board width | Bark pocket    | Permitted, restored up to 50 x 5 mm |
| Colour variation | Permitted slight colour variation                           | Pith           | Permitted                           |
| Knot             | Permitted up to 35 mm, filled                               | Slope of grain | Permitted                           |
| Cracks           | Permitted narrow, filled                                    | Medullary ray  | Permitted                           |

### COSWICK Ltd.

2B Kolasa Str., 223034 Zaslavi, Republic of Belarus

Tel.: +375-17-543-2012, Fax: +375-17-543-2020, E-mail: sales@coswick.com

www.coswick.com

