




# PLANK HARDWOOD FLOORING I TECHNICAL INFORMATION

Product # 1167-3846-30



## DESIGNER SOLUTION COLLECTION DECOR | BERGEN

**Wood species** | Oak  
**Selection** | 1 Common  
**Constructions** | 3-layer flooring T&G  
**Size** | 15x127x600...2100 mm (5/8"x5"x2'...7')  
**Finish** | Silk mat finish

### CONSTRUCTION: 3-LAYER FLOORING T&G

| DIMENSIONS :   |                      |           | PACKAGING :          |                             |
|----------------|----------------------|-----------|----------------------|-----------------------------|
|                |                      |           | BOX                  | PALLET                      |
| Thickness      | 15 mm (5/8")         | Content   | 2 m <sup>2</sup>     | 40 box (80 m <sup>2</sup> ) |
| Width          | 127 mm (5")          | Weigh     | 21 kg                | 842 kg                      |
| Length         | 600...2100 (2'...7') | H x W x L | 128 x 160 x 2 150 mm | 1136 x 810 x 2 163 mm       |
| Average length | 0.98 m (3 1/4')      | Content   | 21,520 sq.ft.        | 860,800 sq.ft.              |
| Microlevel     | 0,5 mm               | Weigh     | 22 lb                | 854 lb                      |
| Joint type     | T&G                  | H x W x L | 5" x 7" x 85" mm     | 45" x 32" x 86" mm          |

### DEVIATIONS:

|                        |                           |                        |
|------------------------|---------------------------|------------------------|
| Deviation on Thickness | ± 0,2 mm                  | EN 13489<br>ГОСТ 862.3 |
| Deviation on Width     | ± 0,2 mm                  |                        |
| Height Difference      | ≤ 0,2 mm on 100 mm length |                        |
| Cup                    | ≤ 0,2 % of width          | EN 13489               |
| Bow                    | ≤ 0,5 % of length         |                        |
| Spring                 | ≤ 0,1 % of length         |                        |

### CHARACTERISTICS:

|                             |                          |          |
|-----------------------------|--------------------------|----------|
| Fire resistance             | Dfl-s1                   | EN 14342 |
| Formaldehyde emission class | E1                       |          |
| Pentachlorophenol content   | None                     |          |
| Thermal resistance          | 0,095 m <sup>2</sup> K/W |          |
| Thermal conductivity        | 0,158 W/(m·K)            |          |
| Structural warranty         | Lifetime                 |          |

### УСТАНОВКА:



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level. Suitable for installation over radiant heating systems.

### УСЛОВИЯ ЭКСПЛУАТАЦИИ И ХРАНЕНИЯ:



— Air humidity 40% – 65%  
— Temperature +18 °C – +22 °C

### FINISH : SILK MAT FINISH

### GRADE : 1 COMMON

| DESCRIPTION:     |   | DESCRIPTION:   |  |
|------------------|---|----------------|--|
| Sound sapwood    | Non-contrasting sapwood is allowed up to 25% of board width | Bark pocket    | Permitted up to 50 mm in length, up to 5 mm in width, filled |
| Colour variation | Moderate contrast allowed                                   | Pith           | Permitted  |
| Knot             | Permitted up to 25 mm, filled                               | Slope of grain | Permitted  |
| Crecks           | Permitted narrow, filled                                    | Medullary ray  | Permitted  |

### COSWICK Ltd.

28 Kolasa Str., 223034 Zaslavl, Republic of Belarus  
Tel.: +375-17-543-2012, Fax: +375-17-543-2020, E-mail: sales@coswick.com  
[www.coswick.com](http://www.coswick.com)

