




# PLANK HARDWOOD FLOORING | TECHNICAL INFORMATION

Product # 1154-1865-10



## DARK WOOD COLLECTION

DECOR | CINNAMON

Wood species | Oak

Selection | Select & Better

Constructions | 3-layer flooring T&G

Size | 19,05x127x600...2100 mm (3/4"x5"x2'...7')

Finish | Silk mat finish

## CONSTRUCTION: 3-LAYER FLOORING T&G

| DIMENSIONS :   |                      |           | PACKAGING :         |                             |
|----------------|----------------------|-----------|---------------------|-----------------------------|
|                |                      |           | BOX                 | PALLET                      |
| Thickness      | 19,05 mm (3/4")      | Content   | 2 m <sup>2</sup>    | 36 box (72 m <sup>2</sup> ) |
| Width          | 127 mm (5")          | Weigh     | 25 kg               | 917 kg                      |
| Length         | 600...2100 (2'...7') | H x W x L | 90 x 275 x 2 155 mm | 1156 x 846 x 2 163 mm       |
| Average length | 0.98 m (3 1/4')      | Content   | 21,520 sq.ft.       | 774,720 sq.ft.              |
| Microlevel     | 0,5 mm               | Weigh     | 26 lb               | 929 lb                      |
| Joint type     | T&G                  | H x W x L | 4" x 11" x 85" mm   | 46" x 33" x 86" mm          |

## DEVIATIONS:

|                        |                           |                        |
|------------------------|---------------------------|------------------------|
| Deviation on Thickness | ± 0,2 mm                  | EN 13489<br>ГОСТ 862.3 |
| Deviation on Width     | ± 0,2 mm                  |                        |
| Height Difference      | ≤ 0,2 mm on 100 mm length |                        |
| Cup                    | ≤ 0,2 % of width          | EN 13489               |
| Bow                    | ≤ 0,5 % of length         |                        |
| Spring                 | ≤ 0,1 % of length         |                        |

## CHARACTERISTICS:

|                             |                          |          |
|-----------------------------|--------------------------|----------|
| Fire resistance             | Dfl-s1                   | EN 14342 |
| Formaldehyde emission class | E1                       |          |
| Pentachlorophenol content   | None                     |          |
| Thermal resistance          | 0,082 m <sup>2</sup> K/W |          |
| Thermal conductivity        | 0,161 W/(m·K)            |          |
| Structural warranty         | Lifetime                 |          |

## УСТАНОВКА:



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level. Suitable for installation over radiant heating systems.

## УСЛОВИЯ ЭКСПЛУАТАЦИИ И ХРАНЕНИЯ:



— Air humidity 40% – 65%  
— Temperature +18 °C – +22 °C

## FINISH : SILK MAT FINISH

## GRADE : SELECT & BETTER

| DESCRIPTION:     |  | DESCRIPTION:   |  |
|------------------|--|----------------|--|
| Sound sapwood    | Non-contrasting sapwood is allowed up to 25% of plank area | Bark pocket    | Permitted up to 10 mm in length, up to 3 mm in width, filled |
| Colour variation | Permitted slight colour variation                          | Pith           | Permitted healthy heart                                      |
| Knot             | Permitted up to 10 mm, filled                              | Slope of grain | Permitted  |
| Crecks           | Not permitted  | Medullary ray  | Permitted  |

## COSWICK Ltd.

2B Kolasa Str., 223034 Zaslavl, Republic of Belarus

Tel.: +375-17-543-2012, Fax: +375-17-543-2020, E-mail: sales@coswick.com

www.coswick.com

