




# CHEVRON 60° | TECHNICAL INFORMATION

Product # 1383-3261-30



## AMERICAN WALNUT COLLECTION DECOR | CLASSIC

**Wood species** | American Walnut  
**Selection** | 1 Natur  
**Pattern** | Chevron  
**Constructions** | 3-layer flooring T&G  
**Size** | 19,05x190x438.78 mm (3/4"x7 1/2"x17 1/4")  
**Finish** | Silk finish

### CONSTRUCTION: 3-LAYER FLOORING T&G

| DIMENSIONS : |                     |           | PACKAGING :        |                       |
|--------------|---------------------|-----------|--------------------|-----------------------|
| Thickness    | 19,05 mm (3/4")     |           | BOX                | PALLET                |
| Width        | 190 mm (7 1/2")     | Content   | 1,667 m2           | 30 box (50,01 m2)     |
| Length       | 438.78 mm (17 1/4") | Weigh     | 21 kg              | 645 kg                |
| Cut angle    | 60°                 | H x W x L | 195 x 395 x 560 mm | 1121 x 800 x 1 750 mm |
| Microbevel   | 0,5 mm              | Content   | 17,937 sq.ft.      | 538,108 sq.ft.        |
| Joint type   | T&G                 | Weigh     | 21 lb              | 669 lb                |
|              |                     | H x W x L | 8" x 16" x 22" mm  | 45" x 32" x 69" mm    |

### DEVIATIONS:

|                           |                   |                        |
|---------------------------|-------------------|------------------------|
| Deviation on Thickness    | ± 0,2 mm          | EN 13489<br>ГОСТ 862.3 |
| Deviation on Length       | ± 0,3 mm          |                        |
| Deviation on Width        | ± 0,2 mm          |                        |
| Angle deviation of planks | ≤ 0,25 mm         |                        |
| Cup                       | ≤ 0,2 % of width  | EN 13489               |
| Bow                       | ≤ 0,5 % of length |                        |
| Spring                    | ≤ 0,1 % of length |                        |

### CHARACTERISTICS:

|                             |               |          |
|-----------------------------|---------------|----------|
| Fire resistance             | Dfl-s1        | EN 14342 |
| Formaldehyde emission class | E1            |          |
| Pentachlorophenol content   | None          |          |
| Thermal resistance          | 0,118 m2·K/W  |          |
| Thermal conductivity        | 0,161 W/(m·K) |          |
| Structural warranty         | Lifetime      |          |

### УСТАНОВКА:



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level.

### УСЛОВИЯ ЭКСПЛУАТАЦИИ И ХРАНЕНИЯ:



— Air humidity 40% – 65%  
— Temperature +18 °C – +22 °C

### FINISH : SILK FINISH

| DESCRIPTION :         |   |
|-----------------------|---|
| Type of coating       | UV-cured modified polyurethane-acrylate |
| Surface (finish) type | Semi-closed pores, wire brushed         |
| Sheen                 | Silk matte 9-18 GU/85°                  |
| Finish warranty       | -                                       |

### CLASSIFICATION SURFACE CHARACTERISTICS:

|                               |                           |          |
|-------------------------------|---------------------------|----------|
| Wear resistance               | Not rated                 | EN 438-2 |
| Scratch resistance            | Not rated                 | EN 438   |
| Slip resistance               | 50 (SRV dry)              | EN 15676 |
| Resistance to chemical agents | Class 5 (Except blue ink) | EN 13442 |
| Repairability                 | Medium                    |          |

### MAINTENANCE AND CARE CONDITIONS :

Maintenance of hardwood floors with Silk finish assumes regular (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with Coswick Hardwood Floor Cleaner or other similar product. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc., should be periodically renewed with special Coswick Restorative Oil. This product restores the protective surface film. Frequency of use depends on type of interior and intensity of foot traffic. For residential interiors, restorative cleaning should be done once in 3-5 years; for public and commercial interiors with intense foot traffic, it is recommended to use the product 2-4 times a year.

### GRADE: 1 NATUR

| DESCRIPTION:     |                               | DESCRIPTION:   |  |
|------------------|-------------------------------|----------------|--|
| Sound sapwood    | No limit                      | Bark pocket    | Permitted up to 50 mm in length, up to 5 mm in width, filled |
| Colour variation | No limit                      | Pith           | Permitted  |
| Knot             | Permitted up to 60 mm, filled | Slope of grain | Permitted  |
| Crecks           | Permitted narrow, filled      | Medullary ray  | Permitted  |

### COSWICK Ltd.

2B Kolasa Str., 223034 Zaslavl, Republic of Belarus  
Tel.: +375-17-543-2012, Fax: +375-17-543-2020, E-mail: sales@coswick.com  
www.coswick.com

