




# MOSAIC FLOORS | TECHNICAL INFORMATION

Product # 1143-1863-10



## GREY SHADOW COLLECTION DECOR | MISTY FJORDS

**Wood species** | Oak  
**Selection** | Select & Better  
**Pattern** | Versailles  
**Constructions** | 3-layer mosaic flooring T&G  
**Size** | 19,05x635x635 mm (3/4"x25"x25")  
**Finish** | Silk mat finish

### CONSTRUCTION: 3-LAYER MOSAIC FLOORING T&G

| DIMENSIONS : |                 |  | PACKAGING : |                   |                      |
|--------------|-----------------|--|-------------|-------------------|----------------------|
|              |                 |  | BOX         | PALLET            |                      |
| Thickness    | 19,05 mm (3/4") |  | Content     | 1,61 m2           | 27 box (43,47 m2)    |
| Width        | 635 mm (25")    |  | Weigh       | 20 kg             | 572 kg               |
| Length       | 635 mm (25")    |  | H x W x L   | 80 x 645 x 645 mm | 916 x 680 x 1 960 mm |
| Microbevel   | 1 mm            |  | Content     | 17,324 sq.ft.     | 467,737 sq.ft.       |
| Joint type   | T&G             |  | Weigh       | 21 lb             | 596 lb               |
|              |                 |  | H x W x L   | 3" x 26" x 26" mm | 36" x 27" x 78" mm   |

### DEVIATIONS:

|                        |                           |                        |
|------------------------|---------------------------|------------------------|
| Deviation on Thickness | ± 0,2 mm                  | EN 13489<br>ГОСТ 862.4 |
| Deviation on Length    | ± 0,3 mm                  |                        |
| Deviation on Width     | ± 0,3 mm                  |                        |
| Height Difference      | ≤ 0,2 mm on 100 mm length |                        |
| Cup                    | ≤ 0,5 % of width          | EN 13489               |
| Bow                    | ≤ 0,5 % of length         |                        |
| Spring                 | ≤ 0,1 % of length         |                        |

### CHARACTERISTICS:

|                             |               |          |
|-----------------------------|---------------|----------|
| Fire resistance             | Dfl-s1        | EN 14342 |
| Formaldehyde emission class | E1            |          |
| Pentachlorophenol content   | None          |          |
| Thermal resistance          | 0,082 m2·K/W  |          |
| Thermal conductivity        | 0,161 W/(m·K) |          |
| Structural warranty         | Lifetime      |          |

### УСТАНОВКА:



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level.

### УСЛОВИЯ ЭКСПЛУАТАЦИИ И ХРАНЕНИЯ:



— Air humidity 40% – 65%  
 — Temperature +18 °C – +22 °C

### FINISH : SILK MAT FINISH

### GRADE : SELECT & BETTER

| DESCRIPTION:     |   | DESCRIPTION:   |  |
|------------------|---|----------------|--|
| Sound sapwood    | Permitted non-contrasting up to 25% of the plank area | Bark pocket    | Permitted up to 20 mm in length, up to 3 mm in width, filled |
| Colour variation | Permitted slight colour variation                     | Pith           | Permitted healthy heart                                      |
| Knot             | Permitted up to 10 mm, filled                         | Slope of grain | Permitted  |
| Crecks           | Not permitted   | Medullary ray  | Permitted  |

#### COSWICK Ltd.

28 Kolasa Str., 223034 Zaslavl, Republic of Belarus  
 Tel.: +375-17-543-2012, Fax: +375-17-543-2020, E-mail: sales@coswick.com  
 www.coswick.com

