




# CHEVRON 60° | TECHNICAL INFORMATION

Product # 1192-4821-30



## DARK WOOD COLLECTION DECOR | OLD VENICE

**Wood species** | Oak  
**Selection** | Tavern  
**Pattern** | Chevron  
**Constructions** | 3-layer flooring T&G  
**Size** | 15x190x438.78 mm (5/8"x7 1/2"x17 1/4")  
**Finish** | Silk mat finish

### CONSTRUCTION: 3-LAYER FLOORING T&G

| DIMENSIONS : |                     |  | PACKAGING :           |                    |
|--------------|---------------------|--|-----------------------|--------------------|
|              |                     |  | BOX                   | PALLET             |
| Thickness    | 15 mm (5/8")        |  | Content               | 2,168 m2           |
| Width        | 190 mm (7 1/2")     |  | Weigh                 | 22 kg              |
| Length       | 438.78 mm (17 1/4") |  | H x W x L             | 195 x 395 x 560 mm |
| Cut angle    | 60°                 |  | Content               | 23,328 sq.ft.      |
| Microbevel   | 0,5 mm              |  | Weigh                 | 23 lb              |
| Joint type   | T&G                 |  | H x W x L             | 8" x 16" x 22" mm  |
|              |                     |  |                       | 30 box (65,04 m2)  |
|              |                     |  |                       | 685 kg             |
|              |                     |  | 1121 x 800 x 1 750 mm |                    |
|              |                     |  | 699,830 sq.ft.        |                    |
|              |                     |  | 710 lb                |                    |
|              |                     |  | 45" x 32" x 69" mm    |                    |

### DEVIATIONS:

|                           |                   |                        |
|---------------------------|-------------------|------------------------|
| Deviation on Thickness    | ± 0,2 mm          | EN 13489<br>ГОСТ 862.3 |
| Deviation on Length       | ± 0,3 mm          |                        |
| Deviation on Width        | ± 0,2 mm          |                        |
| Angle deviation of planks | ≤ 0,25 mm         |                        |
| Cup                       | ≤ 0,2 % of width  | EN 13489               |
| Bow                       | ≤ 0,5 % of length |                        |
| Spring                    | ≤ 0,1 % of length |                        |

### CHARACTERISTICS:

|                             |               |          |
|-----------------------------|---------------|----------|
| Fire resistance             | Dfl-s1        | EN 14342 |
| Formaldehyde emission class | E1            |          |
| Pentachlorophenol content   | None          |          |
| Thermal resistance          | 0,095 m2 K/W  |          |
| Thermal conductivity        | 0,158 W/(m·K) |          |
| Structural warranty         | Lifetime      |          |

### УСТАНОВКА:



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level. Suitable for installation over radiant heating systems.

### УСЛОВИЯ ЭКСПЛУАТАЦИИ И ХРАНЕНИЯ:



— Air humidity 40% – 65%  
 — Temperature +18 °C – +22 °C

### FINISH : SILK MAT FINISH

### GRADE : TAVERN

| DESCRIPTION:     |                                     | DESCRIPTION:   |                          |
|------------------|-------------------------------------|----------------|--------------------------|
| Sound sapwood    | Up to 25% of board width is allowed | Bark pocket    | No limit (after filling) |
| Colour variation | Moderate contrast allowed           | Pith           | Permitted                |
| Knot             | Permitted big, filled               | Slope of grain | Permitted                |
| Crecks           | Permitted wide, filled              | Medullary ray  | Permitted                |

### COSWICK Ltd.

2B Kolasa Str., 223034 Zaslavl, Republic of Belarus  
 Tel.: +375-17-543-2012, Fax: +375-17-543-2020, E-mail: sales@coswick.com  
 www.coswick.com

