




PLANK HARDWOOD FLOORING | TECHNICAL INFORMATION

Product # 1165-3247-10



GREY SHADOW COLLECTION DECOR | PASTEL

Wood species | Oak
Selection | 1 Natur
Constructions | 3-layer flooring T&G
Size | 19,05x300x2950 mm (3/4"x11 13/16"x9 11/16")
Finish | Silk finish

CONSTRUCTION: 3-LAYER FLOORING T&G

| DIMENSIONS : | | | PACKAGING : | |
|---|--------------------|-----------|---------------------|--------------------------------|
| | | | BOX | PALLET |
| Thickness | 19,05 mm (3/4") | Content | 1,77 m ² | 36 box (63,72 m ²) |
| Width | 300 mm (11 13/16") | Weigh | 22 kg | 815 kg |
| Length | 2950 mm (9 11/16") | H x W x L | 44 x 310 x 2 955 mm | 750 x 950 x 3 000 mm |
| Microbevel | 1 mm | Content | 19,045 sq.ft. | 685,627 sq.ft. |
| Joint type | T&G | Weigh | 23 lb | 840 lb |
| Box Content: Occasional broken row consisting from 2 planks (min 600 mm) might occur in every 2nd box | | H x W x L | 2" x 13" x 117" mm | 30" x 38" x 119" mm |

DEVIATIONS:

| | | |
|------------------------|---------------------------|------------------------|
| Deviation on Thickness | ± 0,2 mm | EN 13489 FOCT 862.3 |
| Deviation on Length | - 50 mm | |
| Deviation on Width | ± 0,2 mm | |
| Height Difference | ≤ 0,2 mm on 100 mm length | |
| Cup | ≤ 0,2 % of width | EN 13489 |
| Bow | ≤ 0,5 % of length | |
| Spring | ≤ 0,1 % of length | |

CHARACTERISTICS:

| | | |
|-----------------------------|---------------------------|----------|
| Fire resistance | Dfl-s1 | EN 14342 |
| Formaldehyde emission class | E1 | |
| Pentachlorophenol content | None | |
| Thermal resistance | 0,082 m ² ·K/W | |
| Thermal conductivity | 0,161 W/(m·K) | |
| Structural warranty | Lifetime | |

УСТАНОВКА:



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level.

УСЛОВИЯ ЭКСПЛУАТАЦИИ И ХРАНЕНИЯ:



— Air humidity 40% – 65%
 — Temperature +18 °C – +22 °C

FINISH : SILK FINISH

| DESCRIPTION : | |
|-----------------------|---|
| Type of coating | UV-cured modified polyurethane-acrylate |
| Surface (finish) type | Semi-closed pores, wire brushed |
| Sheen | Silk matte 9-18 GU/85° |
| Finish warranty | - |

CLASSIFICATION SURFACE CHARACTERISTICS:

| | | |
|-------------------------------|---------------------------|----------|
| Wear resistance | Not rated | EN 438-2 |
| Scratch resistance | Not rated | EN 438 |
| Slip resistance | 50 (SRV dry) | EN 15676 |
| Resistance to chemical agents | Class 5 (Except blue ink) | EN 13442 |
| Repairability | Medium | |

MAINTENANCE AND CARE CONDITIONS :

Maintenance of hardwood floors with Silk finish assumes regular (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with Coswick Hardwood Floor Cleaner or other similar product. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc., should be periodically renewed with special Coswick Restorative Oil. This product restores the protective surface film. Frequency of use depends on type of interior and intensity of foot traffic. For residential interiors, restorative cleaning should be done once in 3-5 years; for public and commercial interiors with intense foot traffic, it is recommended to use the product 2-4 times a year.

GRADE: 1 NATUR

| DESCRIPTION: | | DESCRIPTION: | |
|------------------|---|----------------|---|
| Sound sapwood | Non-contrasting sapwood is allowed up to 25% of board width | Bark pocket | Not limited, restored up to 100 x 10 mm |
| Colour variation | Permitted slight colour variation | Pith | Permitted |
| Knot | Permitted up to 60 mm, filled | Slope of grain | Permitted |
| Crecks | Permitted wide, filled | Medullary ray | Permitted |

COSWICK Ltd.

2B Kolasa Str., 223034 Zaslavl, Republic of Belarus

Tel.: +375-17-543-2012, Fax: +375-17-543-2020, E-mail: sales@coswick.com

www.coswick.com

