



# DECLARATION OF PERFORMANCE

DOP – 1.74-06.2026



**1. Unique identification code of the product-type:**

Veneered MDF Wood panels in accordance with EN 622-1-2003, EN 13986:2004+A1:2015

**2. Type, batch, serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):**

Veneered MDF – based acoustic wall and ceiling panels TM COSWICK

**3. Intended use or uses of the construction product in accordance with the applicable harmonised technical specification as foreseen by the manufacturer:**

Wood-based panels for use in construction

**4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):**

COSWICK Ltd., Y. Kolasa str. 2B, Zaslavl, Republic of Belarus, 223034  
TM COSWICK

**5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):**

-

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**

System 4 of appendix ZA of EN 13986:2004+A1:2015

**7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:**

-

**8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:**

-

**9. Declared performance**

| Characteristic                               | Performance declaration        | Harmonized technical specification   |
|----------------------------------------------|--------------------------------|--------------------------------------|
| Thickness                                    | 16.0 mm                        | EN 622-1-2003, EN 13986:2004+A1:2015 |
| Density                                      | $\geq 700 \text{ kg/m}^3$      | EN 622-1-2003, EN 13986:2004+A1:2015 |
| Aging Resistance (Bonding Strength)          | NPD                            | EN 13986:2004+A1:2015                |
| Tensile strength perpendicular to panel face | NPD                            | EN 13986:2004+A1:2015                |
| Emission of formaldehyde                     | E1                             | EN 13986:2004+A1:2015                |
| Reaction to fire                             | D-s2, d0                       | EN 13986:2004+A1:2015                |
| Water vapour permeability                    | wet $\mu=16$ ,<br>dry $\mu=25$ | EN 13986:2004+A1:2015                |
| Sound insulation                             | NPD                            | EN 13986:2004+A1:2015                |
| Sound absorption                             | NPD                            | EN 13986:2004+A1:2015                |
| Thermal conductivity                         | 0.12 W/m*K                     | EN 13986:2004+A1:2015                |
| Content of pentachlorophenol                 | $\leq 5 \text{ ppm}$           | EN 13986:2004+A1:2015                |
| Biological stability                         | Class 1                        | EN 13986:2004+A1:2015                |

NPD – No performance determined

**10. The performance of the product identified in paragraphs 1 and 2 is in conformity with the declared performance in paragraph 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in paragraph 4. Signed for and on behalf of the manufacturer by**

Vladimir Ianovski, director

Zaslavl, 04 June 2026