AQUA WOOD STAIN

COSWICK COATINGS & ADHESIVES

SPECIFICATION



AQUA WOOD STAIN

BENEFITS :

- Easy to use;
- Water-borne;
- Minimal grain raising;
- Even surface toning;
- Creates solid, deep colors and shades.

INGREDIENTS :

Water, polyurethane composition, pigments, functional additives.


Meets the requirements of TV BY 101040134.004-2015 and Complies with Technical Regulations and Applications of Sanitary, Veterinary and Phytosanitary Measures

DESCRIPTION AND APPLICATION :

Waterborne wood stain is a composition of urethane polymers and micronised pigments specifically developed for wood toning.
The stain is designed to decorate unfinished, presanded wooden surfaces: wood floors, stairs, furniture and other wood articles.

APPLICATION :

PREPARATIONS :



1. Sand the surface with an abrasive material with a grit size of 120 –150.



2. Clean the floor from dust and litter using a vacuum-cleaner.



3. It is recommended to provide the following climatic conditions: temperature from +18 °C to +25 °C, relative air humidity 40 – 60 %.

Important! Shake well before use. The product is ready to use and does not require dilution. It is recommended to preliminary test the wood stain on a small sample or a part of sanded surface in order to see the actual finish color.

MANUAL APPLICATION :



1. Apply the wood stain with a rubber trowel distributing it evenly on the surface.



2. After an application rub the wood stain with rugs to the surface removing the excess.



3. Remove excess stain with a cotton cloth.



4. When the first layer is dry, apply the second layer in the same way.


AUTOMATIC APPLICATION :



1. Apply the wood stain with a rubber trowel distributing it evenly on the surface.



2. Remove excess stain with a cotton cloth.



3. Remove the wood stain excess with cotton rags. Rub the wood stain with a single-disk white pad buffing machine



4. When the first layer is dried out, apply the second layer in the same way.

Note: Hard to reach places (corners, joints etc.) should be treated with the use of fine brush or rugs not later than 25 min after the main application.

Coswick Ltd.
2B Kolasa Str., 223034 Zaslavl, Republic of Belarus
Tel.: +375-17-543-2012, Fax: +375-17-543-2020, E-mail: sales@coswick.com
www.coswick.com

AQUA WOOD STAIN

COSWICK COATINGS & ADHESIVES

SPECIFICATION

DRYING TIME :

When applying one layer — 4 hours.
When applying two layers: first layer — 1 hour; second layer – 6 hours

FINISH APPLICAITION :

After the wood stain is completely dry a finish layer of lacquer or oil should be applied.

FLOOR CARE :

We recommend to use care products for hardwood floors.

TOOLS CLEANING :

Tools can be cleaned with water. Remains of dry wood stain can be removed with acetone.

SHELF LIFE, STORAGE AND TRANSPORT CONDITIONS :

12 months from the manufacture date, if package is intact. Keep tightly closed at temperature +5 °C to +25 °C. Keep container dry. Avoid direct sunlight and exposure to temperatures below +5 ° C.

SAFETY REQUIREMENTS :

Intended use only. Avoid contact with skin and mucous membranes. Keep out of reach of children.

DISPOSAL:

This material and its container must be disposed of in accordance with the requirements of legislation on environmental protection and materials disposal.

Coswick Ltd.
2B Kolasa Str., 223034 Zaslavl, Republic of Belarus
Tel.: +375-17-543-2012, Fax: +375-17-543-2020, E-mail: sales@coswick.com
www.coswick.com