CLEANER FOR LACQUERED HARDWOOD FLOORS

COSWICK COATINGS & ADHESIVES

TECHNICAL INFORMATION



CLEANER FOR LACQUERED HARDWOOD FLOORS

BENEFITS :

- Does not leave stains, does not impact the gloss level;
- Gentle and efficient;
- Contains only eco-friendly components;
- Does not contain solvents;
- Tested and approved by the hardwood flooring manufacture

INGREDIENTS :

Water, surfactants, flavors and functional additives

Meets the requirements of ТУ BY 101040134.003-2014 and Complies with Technical Regulation and Application of Sanitary, Veterinary, and Phytosanitary Measures

DESCRIPTION AND APPLICATION :

Cleaner for lacquered hardwood floors is an eco-friendly composition of water-based cleaning agents with light flowery scent. Supplied a in 0,5 liter plastic spray bottle. Ready to use (no need to mix with anything else).

Soft cleaner for everyday care of hardwood floors and laminate flooring, wall panels and solid protective coating as lacquer or lasur.

It may also be used to clean linoleum, vinyl, ceramic and PVC - surfaces cleaning. Provides easy to cleaning and gentle to protective and decorative coatings.

TYPES OF REMOVABLE IMPURITIES :

Food stains:

– grease and oil stains;
– stains from fruits and fruit juice, milk, coffee, tea, non-alcoholic beverages and others.

Household impurities:

– stains from shoes;
– lipstick, ink ribbon and other stains.

PERFORMANCE CHARACTERISTICS :

Reference:	4130-010000
Packing:	0,5 L
Consumption:	500 ml to 210 m^2
pH:	5 – 8
Density:	1,0 g/cm^3
Readiness condition:	Ready to use, does not need to be dissolved
Types of removable impurities:	Most food stains and household impurities
Shelf life:	24 months

MANUAL APPLICATION :

Flooring care (hardwood flooring, flooring plansk, ceramic tiles, linoleum, vinyl, PVC-coatings)

1. Clean the floor from sand, dust and litter using a vacuum-cleaner.
2. Moisture the cleaned surface and the mop with the cleaner concentrate. Move the floor mop toward you and clean the surface thoroughly along the planks. Avoid overwatering of the floor sensitive to humidity. After cleaning the flooring has to be dry in 2-3 minutes.
3. If the mop gets dirty, wash it, wring it out thoroughly and continue cleaning with a clean mop.

If there are any hard-to-remove stains left on the surface (marker, adhesive tape, felt-tip pens, ball pens, shoe polish, nail lacquer and other types of stains) use heavy duty cleaner Coswick .

Different surfaces care (wall panels, furniture, porcelain stoneware slabs, stone)

It is produced in a similar way with a napkin or rag.

Coswick Ltd.
2B Kolasa Str., 223034 Zaslavl, Republic of Belarus
Tel.: +375-17-543-2012, Fax: +375-17-543-2020, E-mail: sales@coswick.com
www.coswick.com

ECO FRIENDLY

СТБ ISO 9001

CLEANER FOR LACQUERED HARDWOOD FLOORS

COSWICK COATINGS & ADHESIVES

TECHNICAL INFORMATION

AUTOMATIC APPLICATION :

1. Fill the tank of an automatic cleaning machine with the necessary amount of cleaner.
2. Clean the surface. If the stains are too heavy, it is recommended to repeat the procedure.

It is recommended to carry out the periodic cleaning not less than once in 4-7 days depending on the soil level.

SHELF LIFE, STORAGE AND TRANSPORT CONDITIONS :

24 months. Store in a cool, dry place with a tightly closed lid. Storage and transportation temperature +5 °C to +25 °C. Protect from frost.

SAFETY REQUIREMENTS :

For intended use only. Avoid contact with mucous membranes. Keep out of reach of children.

DISPOSAL :

This material and its container must be disposed of in accordance with the requirements of legislation on environmental protection and materials disposal.

Coswick Ltd.
2B Kolasa Str., 223034 Zaslavl, Republic of Belarus
Tel.: +375-17-543-2012, Fax: +375-17-543-2020, E-mail: sales@coswick.com
www.coswick.com